

Because our innovations are inspired by you and your patients, the bi-level ventilator BiPAP A40 has been designed to combine ease-of-use and comfort with technological innovations that adapt to your patient's condition to deliver enhanced therapy.

Based on a familiar platform, BiPAP A40 comes with well-known and clinically proven Philips Respironics technology such as Auto-Trak, AVAPS and a Dry Box humidifier design. The device is capable of non-invasive and invasive pressure ventilation, up to 40 cmH₂O, providing treatment for your chronic insufficiency respiratory patients.

BiPAP A40 can provide autonomy and increased support to patients, thanks to its specifically designed battery module.

The device features AVAPS-AE, an innovative mode of ventilation designed to help clinicians during the titration process, while maintaining comfort and therapy optimization. This new ventilation mode helps in providing long-term therapy compliance regardless of changes to the body position, sleep stages and respiratory mechanics.



AVAPS-AE mode

In AVAPS-AE mode, the device monitors the patient's upper airway resistance and automatically adjusts the delivered EPAP required to maintain an airway. Simultaneously, BiPAP A40 automatically adjusts pressure support to maintain a target tidal volume, and when the breath rate is set to Auto, the device will adjust the back-up breath rate based on the patient's spontaneous respiratory rate.

Ordering information	Part no.	
Devices		
BiPAP A40, International*	1111169	

^{*} contains BiPAP A40 ventilator with SD card, power cord, AC power adapter, user manual, ultrafine filter, grey foam filter, tubing, and carrying case

Accessories

A-Series humidifier, International	1111552
A-Series, heated tube humidifier, International	1111555
Battery module	1096770
Detachable battery	1043570
Ultrafine filter kit	1063096
Foam filter kit	1063091
Power supply	1081167
Power cord, Europe	1039014
Power cord, UK	1039026
Power Cord, Canada	1038928
Performance tubing 22 mm	1032907
Performance tubing 15 mm	1074400
EncorePro 2 software	1054785
DirectView software	1005297

BiPAP A40, Auto-Trak, AVAPS, AVAPS-AE, EncorePro, DirectView, and Alice are trademarks of Koninklijke Philips N.V. All rights are reserved.

© 2016 Koninklijke Philips N.V. All rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

Product specifications Ventilation modes

Product specifications	
Ventilation modes	$\cdot CPAP \cdot S \cdot S/T \cdot PC \cdot T \cdot AVAPS\text{-}AE$
Hybrid ventilation	· AVAPS (Average Volume Assured
	Pressure Support)
	· AVAPS-AE
IPAP	4 – 40 cmH ₂ O
EPAP	4 – 25 cmH ₂ O
Target tidal volume	200 – 1500 ml
(AVAPS and AVAPS-AE)	
Breath rate	0 – 40 bpm (4 – 40 bpm in T mode)
Inspiratory time	0.5 – 3 sec
Triggering and cycliing	· Auto-Trak
	Sensitive Auto-Trak
	 Flow triggering
Rise time	1 (100 ms) – 6 (600 ms)
Size	21.6 cm W x 19 cm L x 11.5 cm H
Weight	1.9 kgs (with power supply)
Noise level	< 28 dBA at 10cmH ₂ O
Humidification	System One humidity control and
	'Dry Box' technology
	Heated tube humidification
Alarms	Patient disconnection
	· Apnea
	Low minute ventilation
	· Low tidal volume
	(with AVAPS/AVAPS-AE only)
	High respiratory rate
Monitoring	· Pressure
	· Tidal volume
	Minute ventilation
	Respiratory rate
	· Leak
	· I/E ratio
Battery backup	Detachable battery module: 9h 45
	min at IPAP 12 cmH2O/EPAP 7 cmH ₂ O
	and 12 bpm (restrictive profile)
DC power source	• 12 VDC, 5.0 A (external battery)
	• 24 VDC, 4.2 A (power supply)
	Encore and DirectView software
Data management	
	 Compatible with oximetry module Advanced detection of residual
	respiratory events apnea/hypopnea
	index, obstructed airway apnea,
	hypopnea, periodic breathing,
	RERA, large leak and snore)
Remote control	Compatible with Omnilab Direct
Polygraph and	 Direct connection to Alice PDx and
polysomnograph	Alice6 PSGs
connections	Omnilab Connect to connect to
	most PSG systems



Philips Respironics 1010 Murry Ridge Lane Murrysville, PA 15668 USA